

OVERVIEW

Handyflex is a general-purpose, one-pack acrylic crack repair filler, for interior and exterior use. It forms a water-resistant joint and a dust and damp-proof seal in situations too demanding for normal fillers.

PROPERTIES

- Waterproof
- Weather resistant
- Permanent flexibility (\pm 15%)
- Quick drying
- Easy to apply
- High adhesion to most building surfaces
- Can be painted after 24 hours

AREAS OF USE

- Between concrete elements
- Around doors and windows
- Behind skirtings and architrave
- To repair cracks in plaster and concrete

PREPARATION OF SURFACE

Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges, and protect all adjacent surfaces not to be covered. All cracks, chips, voids and damages should be repaired with an appropriate filler. Apply a coat of Penetrating primer on dusting surfaces.

APPLICATION & CLEANING OF TOOLS

For filling cracks, open up the crack into a "V" shape and prime the surface with Penetrating Primer. Apply a coat of Handyflex and bring flush to the surface. Allow to dry for 24 hours before applying a further coat to counter any shrinkage. Repaint the surface after 24 hours.

Clean tools and equipment with water after use.

HEALTH & SAFETY

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

PACKAGING & STORAGE

Handyflex is supplied in 5kg and 20kg pails.

Store containers in a clean dry area protected from direct sunlight and extreme heat and cold. Unopened containers can be stored for 12 months. Use oldest material first.

TERRACO offers a comprehensive range of products and services for most concrete and finishing needs. Please contact the TERRACO Technical Service Department or your local TERRACO agent for further information, samples, demonstrations and instructor services. The information given in this leaflet is based upon laboratory research, as well as extensive field work and application. All products are sold subject to standard conditions of sale which are available on request. This information is based on TERRACO's present state of knowledge and is intended to provide general information on TERRACO's products and their methods of use. The prospective user is recommended to determine the suitability of TERRACO's suggestions and products before adopting them on a commercial scale.

TECHNICAL DATA

Product	Flexible / paintable crack filler.
Binders	Acrylic co-polymer
Fillers	Fine precisely graded fillers.
Dilution	With water if required.
Specific Gravity	1.40
Colour	White.
Expansion	± 15% of original joint width.
Age Resistance	Excellent
Toxicity	Non-toxic.
Packaging	5kg and 20kg containers.
Storage	12 months in original unopened containers.

For technical enquiries please contact your nearest Terraco representative:

RUSSIA:

OOO Terraco Sweden Ltd, Russia
 Tel: +7 495 1012237
 Fax: +7 495 9273881
 E-mail: terraco@online.ru
 Web: www.terraco.ru

OOO Terraco Vostok Ltd

Tel: +7 (0)4212 410563
 Fax: +7 (0)4212 410591
 E-mail: terracoVostok@terraco.khn.ru

CHINA:

Terraco Architectural Coatings China Co., Ltd.
 Tel: +86 (0)20 8759 4742
 Fax: +86 (0)20 8526 8056
 E-mail: sales@terraco.com.cn
 Web: www.terraco.com.cn

Terraco Chemical (Shanghai) Co., Ltd.

Tel: +86 (0)21 6226 8903
 Fax: +86 (0)21 6252 0547
 Email: shanghai@terraco.com.cn
 Web: www.terraco.com.cn

JORDAN:

Jordan Swedish Polymers Industrial Corp.
 Tel: +962 (0)6 552 7140, 5530229, 5514037
 Fax: +962 (0)6 553 6560
 E-mail: terraco@nol.com.jo
 Web: www.terraco.jo

EGYPT:

Terraco Egypt Chemical Industries S.A.E.
 Tel: +20 (0)2 3479106, 3024860
 Fax: +20 (0)2 3470895
 E-mail: terraco@terraco.com.eg
 Web: www.terraco.com.eg

UAE:

Terraco UAE Ltd
 Tel: +971 (0) 4 2850999
 Fax: +971 (0)4 2852299
 E-mail: terraco@emirates.net.ae

TURKEY:

Terraco Yapi Malzemeleri Sanayi Ve Ticaret AS
 Tel: +90 (0)222 236 0423 / 24
 Fax: +90 (0)222 236 0425
 E-mail: terraco@terraco.com.tr
 Web: www.terraco.com.tr

THAILAND:

Terraco Industry (Thailand) Limited
 Tel: +66 (0)2 948 5558
 Fax: +66 (0)2 948 5540
 E-mail: terraco@terraco.co.th

VIETNAM:

Terraco Vietnam Co., Ltd
 Tel: +84 (0)650 820100
 Fax: +84 (0)650 820101
 E-mail: terraco_vietnam@hcm.vnn.vn

SOUTH KOREA:

Terraco Korea Co., Ltd
 Tel: +82 (0) 2 5611551
 Fax: +82 (0)2 5611515
 E-Mail: terraco@terraco.co.kr
 Web: www.terraco.co.kr

IRELAND:

Terraco Technical Centre, Ireland
 Tel: +353 (0) 404 66555
 Fax: +353 (0) 404 66654
 E-mail: terraco@eircom.net
 Web: www.terraco.com